Forrester Manufacturing Co., Inc.
5073 Bristol Industrial Way
Buford, GA 30518
Toll Free 866-256-4499

SECTION 03 3000

CAST-IN-PLACE CONCRETE

PART 1 - GENERAL

1.01 SUBMITTALS

A. Shop drawings:
1. Column block-outs; stay in-place: Indicate size, configuration and quantity. Shop drawings to be prepared by Forrester Mfg Company, Inc., 5073 Bristol Industrial Way, Buford, Georgia 30518. Phone: 866-256-4499.

PART 2 - PRODUCTS

2.01 MATERIALS

A. Formwork:
1. Column block-outs; stay in-place:
a. Product standard of quality: Forrester Mfg Company, Inc., 5073 Bristol Industrial Way, Buford, Georgia 30518; Pocket-Form Isolator. (866) 256-4499.
b. Characteristics:
1) Material: High content recycled high density polyethylene, HDPE, multi-piece integrally reinforced stay in-place form.
2) Size: As required by column base plate size and depth of column footing below finish slab elevation.
3) Accessories; furnish:
a) Locking Lift Brackets (LLB's) for complete installation.
b) Flush fitting removable safety cover meeting OSHA safety requirements. (for 24" and or 28" square units only.)

PART 3 - EXECUTION

3.01 INSTALLATION

A. Forms:
1. Column block-outs; stay in-place:
a. Install stay in-place forms at columns at grade on footing in accord with manufacturer's installation instructions.
b. Use Locking Lift Brackets (LLB's) to level form top to finish slab level; secure form to footing.
c. Install safety cover over completed pocket form installation immediately.
d. Leave form in place after concrete pour; remove safety cover just prior to casting. Clean form void interior of deleterious material prior to casting.

END OF SECTION 03 3000